



Proven **quality**. Professional **advisory**. Best **service**.

### Product description:

Edge insulation strips by Fair Insulation are made of non-crosslinked polyethylene foam. Thanks to their properties, they eliminate the harmful effects of concrete subfloor motions and stresses that can lead to cracks on surface.

### Application:

Dilatation layer between walls and floors in single- or multi-family housing as well as in public utility buildings and general construction such as pavements or bridges.



### Product advantages:

- ✓ **universal application**
- ✓ **easy assembly**
- ✓ **facilitates optimal thermal and acoustic insulation**
- ✓ **resistance to moisture**
- ✓ **subfloor tensions elimination**
- ✓ **cracks prevention**
- ✓ **limitation of thermal losses**



### Installation:

1. Choose the right product variant bearing in mind application and practicality.
2. Place the strip vertically to create the most sealed connection.
3. if necessary, the excess product should be torn off or cut off .

**PLEASE NOTE THAT THE PRODUCT WIDTH SHOULD BE CHOSEN ACCORDING TO THE THICKNESS OF FLOOR LAYERS. ALWAYS LEAVE SOME EXCESS AMOUNT OF INSULATION STRIP ABOVE THE FLOOR SURFACE.**



### Technical parameters:

INDEX	Height	Thickness	Length	PE density	PE color	Cuts	Glue strip on PE	Overlap	Glue strip on overlap
PY 0003	15 cm	8 mm	25 m	25 kg/m <sup>3</sup>	Blue	yes, 5	no	no	no
PY 0004	15 cm	8 mm	50 m	25 kg/m <sup>3</sup>	Blue	yes, 5	no	no	no
PY 0007	15 cm	8 mm	25 m	25 kg/m <sup>3</sup>	Blue	yes, 5	no	yes, 18 cm	no
PY 0008	15 cm	8 mm	50 m	25 kg/m <sup>3</sup>	Blue	yes, 5	no	yes, 18 cm	no
PY 0011	15 cm	8 mm	25 m	25 kg/m <sup>3</sup>	Blue	yes, 5	yes, 3 cm	no	no
PY 0012	15 cm	8 mm	50 m	25 kg/m <sup>3</sup>	Blue	yes, 5	yes, 3 cm	no	no
PY 0015	15 cm	8 mm	25 m	25 kg/m <sup>3</sup>	Blue	yes, 5	no	yes, 18 cm	yes, 3 cm
PY 0016	15 cm	8 mm	50 m	25 kg/m <sup>3</sup>	Blue	yes, 5	no	yes, 18 cm	yes, 3 cm
PY 0023	15 cm	8 mm	25 m	25 kg/m <sup>3</sup>	Blue	yes, 5	yes, 3 cm	yes, 18 cm	yes, 3 cm
PY 0024	15 cm	8 mm	50 m	25 kg/m <sup>3</sup>	Blue	yes, 5	yes, 3 cm	yes, 18 cm	yes, 3 cm
PY 0027	15 cm	8 mm	25 m	25 kg/m <sup>3</sup>	Yellow	yes, 5	no	no	no
PY 0028	15 cm	8 mm	50 m	25 kg/m <sup>3</sup>	Yellow	yes, 5	no	no	no
PY 0031	15 cm	8 mm	25 m	25 kg/m <sup>3</sup>	Yellow	yes, 5	no	yes, 18 cm	no
PY 0032	15 cm	8 mm	50 m	25 kg/m <sup>3</sup>	Yellow	yes, 5	no	yes, 18 cm	no
PY 0035	15 cm	8 mm	25 m	25 kg/m <sup>3</sup>	Yellow	yes, 5	yes, 3 cm	no	no
PY 0036	15 cm	8 mm	50 m	25 kg/m <sup>3</sup>	Yellow	yes, 5	yes, 3 cm	no	no
PY 0039	15 cm	8 mm	25 m	25 kg/m <sup>3</sup>	Yellow	yes, 5	no	yes, 18 cm	yes, 3 cm
PY 0040	15 cm	8 mm	50 m	25 kg/m <sup>3</sup>	Yellow	yes, 5	no	yes, 18 cm	yes, 3 cm
PY 0047	15 cm	8 mm	25 m	25 kg/m <sup>3</sup>	Yellow	yes, 5	yes, 3 cm	yes, 18 cm	yes, 3 cm
PY 0048	15 cm	8 mm	50 m	25 kg/m <sup>3</sup>	Yellow	yes, 5	yes, 3 cm	yes, 18 cm	yes, 3 cm

### Certifications:

NORM	NUMBER
REFERENCE STANDARD	PN-EN 14313

### Packaging:

Collective packaging 7 rolls with 25 or 50 lm in a bag.

FTL: 60 000 lm.

Material thickness tolerance: 6,5 - 8,5 mm

Length tolerance: 0,5%



You can find more information about products on the webpage: [www.fairpackaging.com/en/news/edge-strips/](http://www.fairpackaging.com/en/news/edge-strips/)